

GFNT2-W

20 Amp, 125 Volt Receptacle/Outlet, 20 Amp Feed-Through, Self-test SmartlockPro Slim GFCI, monochromatic, Residential/Commercial applications, back and side wired, heavy duty, wallplate/faceplate and self grounding clip included - White




Color :  White

UPC Code : 078477712764

Country Of Origin : China

RoHS Compliant : Yes



Available Colors :



Black



Brown



Gray



Ivory



Light Almond



Red

- **SAFE** - Delivers continuous ground fault protection
- **SELF TESTING** - Automatically self-tests to ensure it can respond to ground fault
- **SIMPLE** - Status indicator light provides simple, intuitive feedback

Technical Information

Product Features

Amperage : 20 A

At Rated Voltage : 1 HP

Brand : SmartlockPro

Color : White

Feature : Self-Test

Fed Spec WC-596 : Yes

Grade : Residential/Commercial Specification Grade

Grounding : Self-Grounding

NEMA : 5-20R

Pole : 2

Standards and Certifications : UL/CSA, NEMA WD6, NEMA WD1

Strap Material : Galvanized Steel

Tamper Resistant : No

Termination : Back & Side

Trip Level : Class A, 5mA plus or minus 1mA

Type : Standard Duplex

Voltage : 125 VAC

Wallplate : Included

Warranty : 2-Year Limited

Wire : 3

AC Horsepower Ratings

At Rated Voltage : 1 HP

Dielectric Voltage : Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06

Short Circuit Current Rating : 10KA

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Electrical Specifications

Dielectric Voltage : Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06

Operating Temperature : -35C to +66C

Short Circuit Current Rating : 10KA

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Environmental Specifications

Body Material : Polycarbonate

Clamps : Brass

Grounding Screw : Plated Steel

Line Contacts : Brass Triple-Wipe .031 Thick

Notes : w/ Wallplate

Product ID : Ratings are permanently marked on device

Terminal Accm. : 14-10 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Terminal Screws : Plated Steel

Yoke : Zinc-Plated Steel

Mechanical Specifications

Amperage : 20 A

Body Material : Polycarbonate

Brand : SmartlockPro

Color : White

Face Material : Thermoplastic

Feature : Self-Test

Fed Spec WC-596 : Yes

Grade : Residential/Commercial Specification Grade

Grounding : Self-Grounding

NEMA : 5-20R

Notes : w/ Wallplate

Pole : 2

Product ID : Ratings are permanently marked on device

Standards and Certifications : UL/CSA, NEMA WD6, NEMA WD1

Strap Material : Galvanized Steel

Tamper Resistant : No

Terminal Accm. : 14-10 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Termination : Back & Side

Torque Range : 14 – 18 in.-lbs

Trip Level : Class A, 5mA plus or minus 1mA

Type : Standard Duplex

Voltage : 125 VAC

Warranty : 2-Year Limited

Wire : 3

Standards and Certifications

Face Material : Thermoplastic	ANSI : C-73
Grounding Screw : Plated Steel	CSA C22.2 No. 42 : Yes
Line Contacts : Brass Triple-Wipe .031 Thick	CSA-C22.2 No. 144.1-06 : File LR-57811
Notes : w/ Wallplate	Fed Spec WC-596 : Yes
Operating Temperature : -35C to +66C	MIL-SPEC : A-A-55459-SB
Terminal Screws : Plated Steel	NOM : Yes
Yoke : Zinc-Plated Steel	UL 943 : File E48380
Material Specifications	UL498 : Yes
Body Material : Polycarbonate	
Clamps : Brass	
Face Material : Thermoplastic	

Features and Benefits

- Provides continuous ground fault protection – detects and trips on actual ground fault even when self-test is being conducted
- On initial power up, tests the GFCI within 3 seconds
- Auto-monitoring exceeds the UL requirement
- Auto adapts and shifts to more frequent testing if potential problem is detected
- Status Indicator Light provides simple, intuitive feedback on power and protection status as well as indication of line/load reversal
- Patented Lockout Action prevents reset if GFCI is damaged and cannot respond to a ground fault
- Electronics are designed to minimize any false triggers
- Reduced depth makes it easier to install in any electrical box, even shallow ones
- Terminals allow for easy wiring options – back and side wire capable
- External back wire clamps provide visual indication of proper wire seating
- Withstands high torque and resists wire pullout
- Standard brass self-grounding clip
- Trip threshold meets or exceeds UL requirements for tripping time
- Improved immunity to high-frequency noise reduces nuisance tripping
- Advanced electronics design provides superior resistance to electrical surges and over-voltages
- Compatible with all Decora devices and wallplates; available in select Decora colors
- UL Fed Spec WC-596 rated

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/> <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

