


# 16441-T



Color :  Light Almond

UPC Code : 078477272992

Country Of Origin : Please Contact Customer Service.



Available Colors :



Ivory



White

Decora Plus Single Receptacle Outlet, Commercial Specification Grade, Smooth Face, 20 Amp, 250 Volt, Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - Light Almond

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

## Technical Information

AC Horsepower Ratings

**At Rated Voltage : 2 HP**

Electrical Specifications

**Amperage : 20 A**

**Current Limiting : Full Rated Current**

**Dielectric Voltage : Withstands 2000V per UL498**

**Grounding : Self-Grounding**

**Pole : 2**

**Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current**

**Voltage : 250 VAC**

**Wire : 3**

Environmental Specifications

**Flammability : Rated V-2 per UL 94**

**Operating Temperature : -40°C to 60°C**

Material Specifications

**Body Material : Thermoplastic Nylon**

**Clamp Nuts : Zinc-Plated Steel**

**Color : Light Almond**

**Face Material : Thermoplastic Nylon**

**Ground Clips : Brass-Plated**

**Grounding Screw : Brass 8-32**

**Line Contacts : Brass Triple-Wipe .031 Thick**

**Strap Material : Zinc-Plated Steel**

**Terminal Screws : Brass 10-32**

Mechanical Specifications

**Product ID : Ratings are permanently marked on device**

**Terminal Accom. : 14-10 AWG**

**Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral**

**Termination : Side Wire**

Product Features

**Brand : Decora Plus**

**Color : Light Almond**

**Device Type : Single Receptacle Outlet**

**Feature 4 : Smooth Face**

**Grade : Commercial Specification Grade**

**NEMA : 6-20R**

Standards and Certifications

**ANSI : C-73**


**NEMA : WD-6**

**NOM : 057**

**UL498 : File E13399**

**Warranty : 10-Year Limited**

## Wiring Diagram



6-15R

**SPECIFICATION SUBMITTAL**

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>
JOB NUMBER: <input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)