



UPC Code : 078477801109

Country Of Origin : Please Contact Customer Service.

RoHS Compliant : Yes



2310

20 Amp, 125 Volt, NEMA L5-20R, 2P, 3W, Flush Mtg Locking Receptacle, Industrial Grade, Grounding, V-0-MAX - BLACK

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

- Ideal for motor loads, such as shop vacs and pool pumps, and generators

Technical Information

Mechanical Specifications

Cord Range : 0.385 to 0.780

Product ID : Ratings and NEMA I.D. permanently marked on device

Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-8 AWG

Terminal ID : Marked on Device

Termination : Back & Side

Torque Range : 14-16 in-lbs

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -40°C to 60°C

Material Specifications

Base Material : Valox, Valox

Body Material : Nylon

Color : Black

Cover Material : Valox 357

Face Material : Ultramid, Ultramid

Ground Clips : Nickel-Plated Brass

Ground Contacts : Brass

Grounding Screw : Chromated Brass

Line Contacts : Brass

Strap Material : Nickel-Plated Brass

Terminal Clamps : Zinc-Plated Brass

Terminal Screws : Chromated Brass

Product Features

Base Material : Valox, Valox

Color : Black

Face Material : Ultramid, Ultramid

NEMA : L5-20R

Warranty : Limited Lifetime Warranty, Limited Lifetime Warranty

Standards and Certifications

ANSI : C-73

CSA : C22.2 No. 42

NEMA : WD-1 & WD-6

NOM : 057

UL : 498

UL Fed Spec : W-C-596


UL Fed Spec WC-596 : File E13399

UL498 : File E13399

Warranty

Warranty : Limited Lifetime Warranty, Limited Lifetime Warranty

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

