



UPC Code : 078477809808

Country Of Origin : Mexico

RoHS Compliant : Yes



2330

20 Amp, 277 Volt, NEMA L7-20R, 2P, 3W, Flush Mtg Locking Receptacle, Industrial Grade, Grounding, V-0-MAX - BLACK

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

Technical Information

Mechanical Specifications

Cord Range : 0.595 to 0.895

Product ID : Ratings and NEMA I.D. permanently marked on device

Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-8 AWG

Terminal ID : Marked on Device

Termination : Back & Side

Torque Range : 14-16 in-lbs

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 277 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -40°C to 60°C

Material Specifications

Base Material : Valox, Valox

Body Material : Nylon

Color : Black

Cover Material : Valox 357

Face Material : Ultramid, Ultramid

Ground Contacts : Brass

Grounding Screw : Chromated Brass

Line Contacts : Brass

Strap Material : Nickel-Plated Brass

Terminal Clamps : Nickel-Plated Brass

Terminal Screws : Chromated Brass

Product Features

Base Material : Valox, Valox

Color : Black

Face Material : Ultramid, Ultramid

NEMA : L7-20R

Warranty : Limited Lifetime Warranty, Limited Lifetime Warranty

Standards and Certifications

ANSI : C-73

CSA : C22.2 No. 42

NEMA : WD-1 & WD-6


NOM : 057

UL : 498


UL Fed Spec : W-C-596

Warranty

Warranty : Limited Lifetime Warranty, Limited Lifetime Warranty



Wiring Diagram



L7-20R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

