


## 803 Series Flanged × Mechanical Joint NRS Gate Valve

- PRESSURE RATING: 300 PSI
- UL LISTED AND FM APPROVED







COMPONENTS							
NO.	PART NAME	MATERIAL					
1	BODY	DUCTILE IRON ASTM A536 65-45-12					
2	WEDGE	DUCTILE IRON EPDM ENCAPSULATED					
3	WEDGE NUT	ASTM C67400					
4	STEM	STAINLESS STEEL AISI 420					
5	O-RING	EPDM					
6	BONNET	DUCTILE IRON ASTM A536 65-45-12					
7	O-RING	EPDM					
8	PACKING	GRAPHITE					
9	O-RING	EPDM					
10	THRUST COLLAR	ASTM C67400					
11	O-RING	EPDM					
12	O-RING	EPDM					
13	BOLTS	STAINLESS STEEL AISI 304					
14	NUT CAP	DUCTILE IRON ASTM A536 65-45-12					
15	PLUG (OPTIONAL)	MALLEABLE IRON					

DIMENSIONS						(INCHES)
SIZE	3"	4"	6"	8"	10"	12"
L	8 3/4	9 1/2	11	12	13 7/8	14 7/16
H	11 5/8	13 3/4	17 15/16	21 7/16	25 3/8	28 3/4

All information contained herein is supplied by manufacturer and deemed to be accurate. Information is subject to change without notice. Purchaser is responsible for proper installation, use and maintenance of product. Southern Valve & Fitting USA, Inc. passes on manufacturer's warranty but extends no other warranty. All products sold by Southern Valve & Fitting USA, Inc. are subject to its full terms and conditions of sales as published and available on request. Any warranty made extends to original purchaser and is not assignable or transferable.